

# FAS-06

## 6-inch Active Monitor Speaker

### INTRODUCTION

The FAS-06 is a two-way system designed for near-field monitoring in control rooms and recording studios, as well as high-quality sound reinforcement applications in studio video conferencing scenarios.

The FAS-06 uses a high-quality 1-inch natural silk membrane tweeter and a 6-inch woofer, and the sound cone is made of high-strength tensile fiberglass fiber and sandwich composite molding technology. The FAS-06 is optimized to provide clear and loud sound reproduction for a wide range of applications.



### FEATURES

- Adopt AB class power amplifier module, built-in soft pressure limiter, high-fidelity output playback, delicate and soft sound;
- 50 Hz-20000 Hz ultra-wide frequency response;
- Precision directional tweeter waveguide;
- It has rich input interfaces such as XLR/RCA/TRS;
- Front guide hole design, low distortion, purer sound;

### SPECIFICATIONS

Model	M-6A
name	6-inch professional powered monitors
Frequency response	50Hz-20KHz
Total power	150W Peak,75W RMS;

## FAS-06

Treble power	50W Peak,25W RMS;
Bass power	100W Peak,50W RMS;
Maximum SPL @1m	108dB
Dispersion Angle (HxV)	110°x 110°
Woofer	6"
Tweeter	1"
Enter sensitivity	-2dBu
Gain control	0dBu~ - ∞ ;
Enter the connector	XLR/RCA/TRS;
Signal-to-noise ratio	≧ 85dB
Input impedance	20KΩ
Dimensions (WxHxD)	225x320x280mm
weight	10.5 kg

**FAS-06**